



Room Divider/Cubicle/ Shower Rail Systems





Room Divider/Cubicle/Shower Rail System

Silent Gliss® 6100




Product Information

- For over 40 years the most widely used hospital cubicle system in the world
- Also used for many varied industrial and commercial applications
- Attractive profile combines mechanical strength and flexibility with the smoothest performance
- The design detail gives rigidity and strength with great flexibility in layout whilst achieving a clean unbroken line in hospital wards
- The top channel maximises connection positions and suspension variations. The dust cover strip reduces the risk of cross infection
- Quick release safety device is available through distributors for high risk areas, (see System 6650)
- Stand colour silver. Also available in white
- Standard lengths 6101 in metres: 4.5m, 4.75m, 5.0m, 5.25m, 5.5m, 6.0m, 6.75m, 7.5m (silver only). Profile connector available (177.17", 187", 196.85", 206.69, 216.54, 236.22", 265.74", 295.28")
- For medium to heavy curtains
- An exclusive network of skilled distributors measure, supply and fix all hospital contracts in the U.K. and Eire
- Conforms to HTM66
- White profile incorporates BioCote anti-microbial coating as standard



6100

Profile, Bending and Specification Information



Standard radius 7.87 in.

The standard radius is recommended for optimal operation. The minimum possible radius is 150mm.

6109 An alternative profile to be used for reversible shower rails or uplighter systems (available through distributors).

Specification Guide - download from www.silentgliss.co.uk (password required).

Silent Gliss 6100 cubicle track system, anodised aluminium rail type 6101, secured to fittings detailed below by approved local distributor. Allow for noggins in suspended ceiling/hollow partitions elsewhere in B of Q.

Pre-forming bending running length 90/135 degrees.

Dust cover 6110 fitted to track.

Nylon glider/hook 6147 fitted to track at 10/metre.

Delrin all support 6609 twice screwed/plugged to wall and fitted to track.

Wall bracket 6503/ anodised aluminium 50mm wide (two per set), each bracket screwed/plugged to wall and fitted to track.

Delrin end cover 6611 secured to track.

End stop 6007 secured to track.

Connexing bridge 6512, anodised aluminium secured to track.

T-Junction 6514, anodised aluminium secured to track.

Double T-junction 6525, anodised aluminium secured to track.

Internal connecting bridge secured to track.

Ceiling fixing plate 6137, anodised aluminium (single), once screwed through ceiling to noggin above (noggin by others)/plugged and screwed and secured to track.

Double ceiling fixing plate 6138, anodised aluminium twice screwed through ceiling to noggin above (noggin by others)/plugged and screwed and secured to track.

6190 Hanger, anodised aluminium assembly drop m once screwed through ceiling to noggin above (noggin by others)/plugged and screwed and secured to track.

6501 V-hanger, anodised aluminium assembly drop m twice screwed through ceiling noggins (noggins by others)/plugged and screwed and secured to track.




6100

System Layout Options


As a universal room divider system with various accessories, there are few limits to size and layouts. The recommended height from floor level to the underside of the track is 2100mm.

Typical layout for hospital (without V-hangers)



A: hanger rod 6190
B: wall support 6609
C: bracket 6503

Typical layout for hospital (with use of V-hangers)





A: hanger rod 6190
B: wall support 6609
D: V-hanger 6501

Lateral stability in any cubicle layout is essential to prevent weakening of the wall and ceiling fixtures by lateral movement. Where it is not practical to fit tie bars etc., stability may be obtained by the incorporation of V hangers to the ceiling as shown in the diagram above.

Fitting Information

The System 6100 is normally ceiling and wall fixed on suspended hangers and special wall brackets.


Site preparation for suspended ceiling applications



Fixings should support the ends of the profile and any changes in direction. Maximum span between fixings is **118.11in**. When fitting to suspended ceilings site preparation is critical. At each hanger position a noggin in approved material is required above the suspended ceiling; underside to rest on top of ceiling (but independently supported) with a minimum length of **11.81"** at right angles to the track in which the hanger occurs to give fixing tolerance. Ideally the hangers should be on the return track, if on the front track then adequate support should be provided. A detailed information sheet is available on request.




6100



Diagonal fixing supports can be used to return the hanger to the bedhead wall, but only for use when it is impossible to ceiling fix.



Dust Cover Strip




Dust cover strip 6110 for profile 6101 (6108 for profile 6109), it reduces the risk of cross infection.

Fitting Options


Ceiling fix with fixing plates



6124
Twist fixing plate





6137
Ceiling fix bracket



6138
Ceiling fix bracket
double (42mm)(1.65")

Fixing plate positioning is recommended at maximum 11.81 in. intervals.

Ceiling fix with ceiling support 6175





6175
Ceiling support

Bracket positioning is recommended at maximum 300mm intervals.


Ceiling fix with hanger rod 6190



6100




6190
Hanger rod assembly



6609
Wall support


Can also be fixed through suspended ceilings by using special sleeves 6197, 6187, 6188

Ceiling fix with V-hanger 6501




Lateral stability in any cubicle layout is essential to prevent weakening of the wall and ceiling fixtures by lateral movement. V-hangers (25°-35°) provide alternative lateral stability when not practical to fit tie bars and to stabilise straight track over 3 metres. (118.11")



Wall fix at 90° to wall



Profile Junctions (join lengths at 90°)




Profile Connecting bridge 6512 (bent applications)




6100

Wall fix with bracket 6503(a-g)



| | (in.) | (in.) |
|-------|-------------|-------------------|
| 6503a | 1.97"x1.97" | 6503b 7.87"x1.97" |
| 6503c | 1.97"x3.94" | 6503d 3.94"x1.97" |
| 6503e | 0.98"x1.97" | 6503f 3.94"x3.94" |
| 6503g | 2.95"x5.9" | |



Standard Accessories

6007 Endstop



6065 Twist eye endstop



6083 Glider



6086 Spring stop



6094 Roller glider with hook



6096 Glider 6083 in strip form



6098 Roller glider with eye



6101 Profile



6110 Dust cover



6124 Twist fixing plate



6137 Ceiling fix bracket



6138 Ceiling fix bracket double (42mm)



6143 Glider 6144 in strip form



6146 Hook



6147 Glider 6144 with hook 6146 in strip form




6175 Ceiling support




6187 Dummy ceiling support sleeve




6199 Internal connecting bridge



6503 Wall bracket (various sizes)




6512 Connecting bridge



6514 T-Junction



6525 Cross connection



6609 Wall support



6611 Endcover



6628 V-hanger track insert



Sets

6190 Hanger rod assembly

6194 Track insert

1



| | | | | | |
|------|-------------------|------|------------------------|---|---|
| | | 6191 | Hanger rod | 1 |  |
| | | 6192 | Sleeve | 1 |  |
| | | 6193 | Ceiling stud | 1 |  |
| 6501 | V-hanger assembly | 6771 | Vine eye | 1 |  |
| | | 6770 | Locking pin | 1 |  |
| | | 6625 | Complete fixing sleeve | 1 |  |
| | | 6519 | Hanger rod | 1 |  |
| | | 6628 | V-hanger track insert | 1 |  |

Optional Accessories


Parts

| | | | | | |
|------|-------------------------|---|------|-----------------|---|
| 6108 | Dustcover for 6109 |  | 6109 | Profile |  |
| 6160 | Connecting piece |  | 6188 | Ceiling support |  |
| 6197 | Hanger joint sleeve |  | 6283 | Roller glider |  |
| 6524 | Diagonal fixing support |  | | | |




6100

Useful Information



The left hand diagram illustrates the standard measurements for 6100 cubicle/shower system with combined 6147 glider/hook. For non medical application refer to the right hand illustration and the figures below for the roller glider dimensions.

6083 = 7mm (0.28")
6094 = 31mm (1.22")
6098 = 26mm (1.02")
6283 = 7mm (0.28")
6144 = 9mm (0.35")





6100

www.SilentGlissAmerica.com

Silent Gliss Inc
United States Distribution
755 East 134th street
3rd Floor.
Bronx, NY 10454

Correspondence:
P.O. Box 592
New York, Ny 10150

Please call or email
with any questions or for technical catalogs:
info@SilentGlissAmerica.com
Tel: 718-412-9040